

HDMI	Gauge Size	Connector	Shield	Rating	Available Lengths	720/60 8 bit	1080/60 8 bit	1080/60 12 bit	4K/30 10G	4K/60 10G	4K/60 18G
MC-HD-XXM	34	Standard HDMI	Copper Foil	Non-Plenum	18", 3', 6', 10'	-	-	up to 10'	up to 6'	X	X
MC-HD2-XX	32	Standard HDMI	Copper Foil	Non-Plenum	18", 3', 6', 10'	-	-	-	-	-	ALL
HDP-XX	30	T-Grip	Foil & Copper Braid	Non-Plenum	3', 6', 10', 15'	-	-	-	-	-	ALL
HDLK-XX	30	Locking	Foil & Copper Braid	Non-Plenum	18", 3', 6', 10'	-	-	-	-	-	ALL
HD-RA-XX	30	T-Grip	Copper Foil	Non-Plenum	3', 6', 10'	-	-	-	-	up to 10'	X
EC-HD28-XXM	28	Standard HDMI	Foil & Copper Braid	Non-Plenum	18", 3', 6', 10', 15'	-	-	-	-	up to 15'	X
HD28-XXRM	28	T-Grip	Foil & Copper Braid	Non-Plenum	25', 35', 50', 75'	-	up to 75'	-	up to 35'	X	X
HD24-XXM	24	T-Grip	Foil & Copper Braid	Non-Plenum	25', 35', 50'	-	up to 50'	up to 35'	up to 25'	X	X
HD24-XXRM	24	T-Grip	Foil & Copper Braid	Non-Plenum	50', 75', 100'	-	up to 100'	up to 75'	up to 50'	X	X
P-HD28-XXRM	28	T-Grip	Foil & Copper Braid	Plenum	25', 35', 50', 75'	-	up to 75'	-	up to 35'	X	X
P-HD24-XXM	24	T-Grip	Foil & Copper Braid	Plenum	6', 16', 25', 35', 50'	-	up to 50'	up to 35'	up to 25'	X	X
P-HD24-XXRM	24	T-Grip	Foil & Copper Braid	Plenum	50'	-	-	-	up to 50'	X	X
P-HDADC-XX	N/A	DP and DVI Options	Fiber Cable	Plenum	35', 50', 75', 100', 150', 200', 250', 300'	-	-	-	-	-	ALL
P-HDAEC-XX	N/A	Standard HDMI	Fiber Cable	Plenum	35', 50', 75', 100', 150'	-	-	-	-	-	ALL
P-HDFH-DC2-XX	N/A	Detachable Head	Fiber Cable	Plenum	32', 49', 75', 98', 164', 196', 262', 328'	-	-	-	-	-	ALL
CEL-UFO-HD-XX	N/A	Detachable Pigtail	Fiber Cable	Plenum	35', 40', 50', 60', 80', 100', 130', 160', 200', 500', 1000'	-	-	-	-	-	ALL
CEL-LUMA-HD-XX	N/A	Standard HDMI	Fiber Cable	Non-Plenum	35', 40', 50', 60', 80', 100'	-	-	-	-	-	ALL
CWP0005-HDF-ACT	30	Standard HDMI F-F	Foil & Copper Braid	Non-Plenum	8"	-	-	-	-	-	ALL

USB						USB C		
	Config	Active	USB Spec	Rating	Available Lengths		Config	Available Length
USB-AA-XX	A male A male	No	USB 2.0	Non-Plenum	1', 3', 6', 10', 15'	V-USBC-USBC	C male C male	3'
USB-AAF-XX	A male A Female	No	USB 2.0	Non-Plenum	1', 3', 6', 10', 15'	V-USBC-MCBM	C male micro B	3', 6'
USBA-AF-XXACT	A male A Female	Yes	USB 2.0	Non-Plenum	16', 25', 35', 50', 75'	V-USBC-USBAM	C male A male	3', 6'
USB-AB-XX	A male B male	No	USB 2.0	Non-Plenum	18", 1', 3', 6', 10', 15'	V-USBC-USB3AM	C male USB 3 A male	3'
USBAB-XXACT	A male B male	Yes	USB 2.0	Non-Plenum	25', 35', 50', 75'	V-USBC-HD	C male HDMI	3', 6', 10'
USB3-AA-XX	A male A male	No	USB 3.0	Non-Plenum	3', 6', 10'	V-USBC-DP	C male DisplayPort	3', 6', 10'
USB3-AAF-XX	A male A Female	No	USB 3.0	Non-Plenum	3', 6', 10'			
USB3-AB-XX	A male B male	No	USB 3.0	Non-Plenum	3', 6', 10'			
CEL-LUMA-USB-XX	A male A Female	Yes	USB 3.0	Non-Plenum	35', 40', 50', 60', 80', 100'			
CWP0011-USB-AA-PT	A Female A Female	No	USB 2.0	Non-Plenum	8"			
CWP0009-USB-AA-ACT	A Female A Female	Yes	USB 2.0	Non-Plenum	8"			
CWP0012-USB-AA-PT	A Female B Female	No	USB 2.0	Non-Plenum	8"			
CWP0010-USB-BA-ACT	B Female A Female	Yes	USB 2.0	Non-Plenum	8"			
P-USBA-AF-XXACT	A male A Female	Yes	USB 2.0	Plenum	25', 35', 50', 75'			
P-USBAB-XXACT	A male B male	Yes	USB 2.0	Plenum	25', 35', 50', 75'			



**Sales Support**  
480.966.2221 x1  
sales@covid.com

**Technical Support**  
480.966.2221 x2  
techsupport@covid.com

1723 W. 4th Street  
Tempe, Arizona 85281

www.covid.com

VGA	Config	3.5MM Audio	EDID	Rating	Available Lengths
VPR1211-XXM	Male To Male	No	Yes	Non-Plenum	3', 6', 10', 15', 25', 35', 50', 75', 100'
VPR1211-XXAM	Male To Male	Yes	Yes	Non-Plenum	3', 6', 10', 15', 25', 35', 50', 75', 100'
MC-VGA-XXM	Male To Male	No	Yes	Non-Plenum	3', 6', 10', 15', 25'
MC-VGAA-XXM	Male To Male	Yes	Yes	Non-Plenum	3', 6', 10', 15', 25'
CWP0002-15HDF-PT	Female To Female	No	Yes	Non-Plenum	8'
P-CVGAID-XXM	Male To Male	No	Yes	Plenum	25', 35', 50', 75'
P-CVGAID-XXM	Male To Male	Yes	Yes	Plenum	25', 35', 50', 75'
P-CVGAMFID-XX	Male To Female	No	Yes	Plenum	25', 35', 50', 75', 100'

DVI		Gauge Size	Config	Rating	Available Lengths
DVI-DIGLL-XXM	(Single-link)	28	M to M DVI-D	Non-Plenum	3', 6', 15', 25', 35', 50', 100''
MC-DVID-XXFM	(Single-link)	30	M to M DVI-D	Non-Plenum	18", 3', 4', 5', 6'
MC-DVII-XXFM	(Single-link)	30	M to M DVI-I	Non-Plenum	5' & 6'
DDVID-XXMV	(Dual-link)	30	M to M DVI-D	Non-Plenum	3', 6', 10', 15', 25', 35', 50'
DDVII-XXMV	(Dual-link)	--	M to M DVI-I	Non-Plenum	3', 6', 10', 15'
DVII-MF-14INCH	(Single-link)	--	M to F DVI-I	Non-Plenum	14'
P-DVID24-XXM	(Single-link)	24	M to M DVID-D	Plenum	25', 35', 50', 75'
P-DVIFH-DC-XX	(Single-link)	--	M to M DVID-D	Plenum	32', 49', 75', 98', 164', 196', 262, 328

DVI-HD	VP-DVI-HD-XX	--	DVI Male to HD Male	Non-Plenum	3', 6', 10', 15'
	DVI-HD24-XX-M	--	DVI Male to HD Male	Non-Plenum	25', 35', 40', 50'
	P-DVID-HD-XX-M	--	DVI Male to HD Male	Plenum	25', 35', 50'

DP	VP-DP-XX	Copper	--	Non-Plenum	3', 6', 10', 15'
	P-DPFH-XX	Fiber	--	Plenum	32', 49', 75', 98', 164', 196', 262', 328'
	CEL-LUMA-DP-XX	Fiber	--	Non-Plenum	35', 40', 50', 60', 80', 100'
	CEL-UFO-DP-XX	Fiber	--	Plenum	35', 40', 50', 60', 80', 100', 130', 160', 200', 500', 1000'

CAT	Config	Construction	Rating	Available Lengths
C5E-RJ-BLK-XX	RJ45 M to M	Cat 5e	Non-Plenum	1', 3', 7', 10', 15', 20', 25', 35', 50', 75', 100'
C5EF-RJ-BLK-XX	RJ45 M to M	Cat 5e Shielded	Non-Plenum	1', 3', 7', 10', 15', 20', 25', 35', 50', 75', 100'
C6-RJ-BLK-XX	RJ45 M to M	Cat 6	Non-Plenum	1', 3', 7', 10', 15', 20', 25', 35', 50', 75', 100'
C6F-RJ-BLK-XX	RJ45 M to M	Cat 6 Shielded	Non-Plenum	1', 3', 7', 10', 15', 20', 25', 35', 50', 75', 100'
V-C6-RJ-XX-XX (multiple colors options)	RJ45 M to M	Cat 6	Non-Plenum	See website for individual color & lengths
V-C6A-RJ-XX-XX (multiple colors options)	RJ45 M to M	Cat 6a	Non-Plenum	See website for individual color & lengths
P-C5E-RJ-BLK-XX	RJ45 M to M	Cat 5e	Plenum	25', 35', 50', 75', 100'
P-C5EF-RJ-BLK-XX	RJ45 M to M	Cat 5e Shielded	Plenum	25', 35', 50', 75', 100'
P-C6-RJ-BLK	RJ45 M to M	Cat 6	Plenum	25', 35', 50', 75', 100'
P-C6F-RJ-BLK	RJ45 M to M	Cat 6 Shielded	Plenum	25', 35', 50', 75', 100'
P-C6AF-RJ-BLK	RJ45 M to M	Cat 6a Shielded	Plenum	25', 35', 50', 75', 100'

Bulk category cable is available in 500', 1,000' or custom lengths.

# Cable Quick Reference

